



# NTN BEARING-BOWER CORP.

3.438 Inch | 87.325 Millimeter x 4.29 Inch |  
 108.966 Millimeter x 3.75 Inch | 95.25 Millimeter  
 LINK BELT PKEB22655FE7 Pillow Block Bearings



Bearing No. PKEB22655FE7

PKEB22655FE7 Bearing 2D drawings and 3D CAD models

|                           |  |
|---------------------------|--|
| Category                  | Pillow Block Bearings  |
| Inventory                 | 0.0  |
| Manufacturer Name         | REXNORD  |
| Minimum Buy Quantity      | N/A  |
| Weight                    | 19.051   |
| EAN                       | 0793699554939  |
| Product Group             | M06288   |
| Number of Mounting Holes  | 4  |
| Mounting Method           | Tapered Adapter Sleeve   |
| Housing Style             | 4 Bolt Pillow Block  |
| Rolling Element           | Spherical Roller Bearing   |
| Housing Material          | Cast Steel   |
| Expansion / Non-expansion | Expansion  |
| Mounting Bolts            | 3/4 Inch   |
| Relubricatable            | Yes  |
| Insert Part Number        | B22655E7L  |
| Seals                     | Triple Lip Contact   |
| Housing Configuration     | 1 Piece Solid  |
| Inch - Metric             | Inch   |
| Other Features            | Double Row   Extended Inner Race   |
| Long Description          | 4 Bolt Pillow Block; 3-7/16" Bore; 3-3/4" Base to Center Height; Tapered Adapter Sleeve Mount; Spherical Roller Bearing; |



## NTN BEARING-BOWER CORP.

|                               |   |
|-------------------------------|---|
|                               | Relubricatable; Cast Steel;<br>Triple Lip Contact;<br>Expansion |
| Category                      | Pillow Block  |
| UNSPSC                        | 31171511  |
| Harmonized Tariff Code        | 8483.20.40.80   |
| Noun                          | Bearing   |
| Keyword String                | Pillow Block  |
| Manufacturer URL              | <a href="http://www.rexnord.com">http://www.rexnord.com</a>     |
| Manufacturer Item Number      | PKEB22655FE7  |
| Manufacturer Internal Number  | 0155493   |
| Weight / LBS                  | 47  |
| B                             | 3.75 Inch   95.25 Millimeter                                    |
| Bolt Spacing Minimum          | 0 Inch   0Millimeter  |
| Nominal Bolt Center to Center | 10 Inch   254 Millimeter  |
| D                             | 4.29 Inch   108.966<br>Millimeter                               |
| Actual Bolt Center to Center  | 10 Inch   254Millimeter   |
| d                             | 3.438 Inch   87.325<br>Millimeter                               |
| Bolt Spacing Maximum          | 0 Inch   0Millimeter  |