



# NTN BEARING-BOWER CORP.



2 Inch | 50.8 Millimeter x 2.344 Inch | 59.538 Millimeter x 2.25 Inch | 57.15 Millimeter SKF SYR 2 NH Pillow Block Bearings

Bearing No. SYR 2 NH

SYR 2 NH Bearing 2D drawings and 3D CAD models

Category	Pillow Block Bearings
Inventory	0.0
Manufacturer Name	SKF
Minimum Buy Quantity	N/A
Weight	4.18
EAN	7316577312334
Product Group	M06288
Number of Mounting Holes	2
Mounting Method	Stepped Sleeve
Housing Style	2 Bolt Pillow Block
Rolling Element	Spherical Roller Bearing
Housing Material	Cast Iron
Expansion / Non-expansion	Non-expansion
Mounting Bolts	5/8 Inch
Relubricatable	Yes
Insert Part Number	22210
Seals	Trigard
Housing Configuration	1 Piece Solid
Inch - Metric	Inch
Other Features	Double Row   Heavy Duty   Locating Bearing   Open End   With Grub Screw
Long Description	2 Bolt Pillow Block; 2" Bore; 2-1/4" Base to Center Height; Stepped Sleeve Mount; Spherical Roller



## NTN BEARING-BOWER CORP.

	Bearing; 5-15/16" Minimum Bolt Spacing; 6-9/16" Bolt Spacing Maximum; Relubricata
Category	Pillow Block
UNSPSC	31171511
Harmonized Tariff Code	8483.20.40.80
Noun	Bearing
Keyword String	Pillow Block
Manufacturer URL	<a href="http://www.skf.com">http://www.skf.com</a>
Manufacturer Item Number	SYR 2 NH
Weight / LBS	9.2
B	2.25 Inch   57.15 Millimeter
D	2.344 Inch   59.538 Millimeter
Bolt Spacing Maximum	6.563 Inch   166.7Millimeter
Bolt Spacing Minimum	5.938 Inch   150.825Millimeter
Nominal Bolt Center to Center	6.3 Inch   160 Millimeter
d	2 Inch   50.8 Millimeter
Actual Bolt Center to Center	0 Inch   0Millimeter
bore diameter:	2.0000 in
bolt center-to-center length:	6-1/4 in
overall length:	8.3750 in
base width:	2-1/16 in
overall height:	4.5625 in
expansion type:	Non-Expansion Bearing (Fixed)
mounting:	Two-Bolt Base
finish/coating:	Uncoated
bearing type:	Spherical Roller
seal type:	Tri-Guard
bore type:	Round



## NTN BEARING-BOWER CORP.

radial dynamic load capacity:	21600 lbf
housing construction:	Solid Pillow Block
radial static load capacity:	22400 lbf
base to bore centerline:	2.2500 in
maximum rpm:	2150 RPM
duty type:	Standard Duty
lubrication type:	Lubrication Fitting
housing material:	Cast Iron
series:	SYR
locking device:	Concentric Collar
replacement bearing:	22210