



# NTN BEARING-BOWER CORP.



1.5 Inch | 38.1 Millimeter x 2.344 Inch | 59.538 Millimeter x 1.875 Inch | 47.63 Millimeter SKF SYR 1.1/2 N Pillow Block Bearings

Bearing No. SYR 1.1/2 N

SYR 1.1/2 N Bearing 2D drawings and 3D CAD models

Category	Pillow Block Bearings
Inventory	0.0
Manufacturer Name	SKF
Minimum Buy Quantity	N/A
Weight	3.18
EAN	7316577312341
Product Group	M06288
Number of Mounting Holes	2
Mounting Method	Stepped Sleeve
Housing Style	2 Bolt Pillow Block
Rolling Element	Spherical Roller Bearing
Housing Material	Cast Iron
Expansion / Non-expansion	Expansion
Mounting Bolts	1/2 Inch
Relubricatable	Yes
Insert Part Number	22208
Seals	Trigard
Housing Configuration	1 Piece Solid
Inch - Metric	Inch
Other Features	Double Row   Heavy Duty   Open End   With Grub Screw
Long Description	2 Bolt Pillow Block; 1-1/2" Bore; 1-7/8" Base to Center Height; Stepped Sleeve Mount; Spherical Roller



## NTN BEARING-BOWER CORP.

	Bearing; 4-11/16" Minimum Bolt Spacing; 5-5/16" Bolt Spacing Maximum; Relubri
Category	Pillow Block
UNSPSC	31171511
Harmonized Tariff Code	8483.20.40.80
Noun	Bearing
Keyword String	Pillow Block
Manufacturer URL	<a href="http://www.skf.com">http://www.skf.com</a>
Manufacturer Item Number	SYR 1.1/2 N
Weight / LBS	7
Bolt Spacing Maximum	5.313 Inch   134.95Millimeter
D	2.344 Inch   59.538 Millimeter
d	1.5 Inch   38.1 Millimeter
B	1.875 Inch   47.63 Millimeter
Bolt Spacing Minimum	4.688 Inch   119.075Millimeter
Nominal Bolt Center to Center	5 Inch   127 Millimeter
Actual Bolt Center to Center	0 Inch   0Millimeter
bore diameter:	1.5000 in
bolt center-to-center length:	5 in
overall length:	6.8750 in
base width:	2-1/16 in
overall height:	3.8750 in
expansion type:	Expansion Bearing (Floating)
mounting:	Two-Bolt Base
finish/coating:	Uncoated
bearing type:	Spherical Roller
seal type:	Tri-Guard



## NTN BEARING-BOWER CORP.

bore type:	Round
radial dynamic load capacity:	21600 lbf
housing construction:	Solid Pillow Block
radial static load capacity:	20000 lbf
base to bore centerline:	1.8750 in
maximum rpm:	2500 RPM
duty type:	Standard Duty
lubrication type:	Lubrication Fitting
housing material:	Cast Iron
series:	SYR
locking device:	Concentric Collar
replacement bearing:	22208